




CHANGSHA TAIHE ELECTRONIC EQUIPMENT CO,.LTD.


Pressure Sensor | Temperature Sensor | Liquid Level Sensor | Load Cell | Smart Instruments

Position sensor |Torque | Internet of Things



PPM-HLW-2A Online Micro Water Sensor for Oil





Product Introduction

The PPM-HLW-2A adopts advanced water content sensitive element and temperature sensitive element, it can measuring water content, water activity and temperature in harsh environment continuously, accurately, fast.


Measuring oil: lubricant oil, hydraulic oil, engine oil, fuel, insulating oil, turbine oil, etc.

Features

- Measuring water activity of oil fast and continuously;
- Measuring water content accurately;
- High stability in harsh area;
- ◆ Small in size.



Wiring Diagram



- 1) Red +24V DC
- 2) White RS485A
- 3) Black GND
- 4) Green RS485B
- 5) Yellow 4~20mA ch1
- 6) Pink 4~20mA ch2





Specification	
Water Activity	
Measuring Range	0~1 aw
Accuracy	0~0.6±0.02 aw 0.6~0.9±0.03 aw 0.9~1±0.04aw
Response Time	< 1 min
Water Content	
Measuring Range	0~2000ppm
Measurement Accuracy	±10%
Temperature	
Measuring Range	-40~+80°C
Accuracy	±0.2°C
Operating Temperature	-40~+60°C
Storage Temperature	-40~+80°C
Oil Temperature Permitted	-40~+120°C
Output Signal	
Digital Output Signal	RS485 MODBUS, RS232 available
Analog Output Signal	4~20mA, 0~20mA resistance load $<$ 500Ω
Others	
Process Connection	G1/2" ISO, 1/2" NPT
Pressure Range	100 bar
Material	Stainless Steel 316L
Ingress Protection	IP66
Power Supply	9~36V DC, load current < 5mA
Weight	200g
Electric Connection	M8*1, 6 core cable, 2m
Certification	CE, EN61326 EN61326-2-3 ICES-003B

CONTACT US

www.csppmsensor.com

Address: No. 188, Huanbao Road, Yuhua Zone, Changsha, Hunan, China

E-mail: info@csppm.com **Mobile | Wechat | WhatsApp:** +86 19118913383